

Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

AD

28516

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by
DOCUMENT SERVICE CENTER
KNOTT BUILDING, DAYTON, 2, OHIO

UNCLASSIFIED

AD No. 28516

ASTIA FILE COPY

Astia

Columbia University
in the City of New York

DEPARTMENT OF CIVIL ENGINEERING



APPLICATION OF GREEN'S METHOD IN DERIVING
APPROXIMATE THEORIES OF ELASTICITY

by

G. HERRMANN

Office of Naval Research Project NR-064-388

Contract Nonr-266(09)

Technical Report No. 13

CU-14-54-ONR-266(09)-CE

February 1954

Columbia University
in the City of New York

DEPARTMENT OF CIVIL ENGINEERING



APPLICATION OF GREEN'S METHOD IN DERIVING
APPROXIMATE THEORIES OF ELASTICITY

by

G. HERRMANN

Office of Naval Research Project NR-064-388

Contract Nonr-266(09)

Technical Report No. 13

CU-14-54-ONR-266(09)-CE

February 1954

ABSTRACT

G. Green's procedure of deriving the three-dimensional linear equations of the theory of elasticity, is used as a guide in deducing an approximate theory of longitudinal motions of an elastic rod which contains the effects of radial inertia and radial shear deformation. At various stages of the development, attention is drawn to the analogies between the three-dimensional and the approximate theory. It is noted in particular, that the principle of conservation of energy imposes restrictions on possible stress-strain relations. These restrictions, which were overlooked in a previous paper by Mindlin and Herrmann, are taken into account here, thus altering the displacement equations of motion, but leaving the wave velocities in an infinite rod unchanged.

APPLICATION OF GREEN'S METHOD
IN DERIVING APPROXIMATE THEORIES OF ELASTICITY

Introduction

Various procedures have been adopted in establishing approximate linear theories of equilibrium and motion of elastic bodies, one or two of whose dimensions are small in comparison with the others.

One possibility consists in applying Newton's second law with respect to an element of the body, restricting possible deformations or stress distributions. It was followed, for example, by Bernoulli and Euler¹ in deriving what is termed today the elementary beam theory.

Another possibility consists in operating in appropriate fashions upon the general three-dimensional equations, as was demonstrated by Boussinesq [2] in deriving classical plate equations.

More recently, plate theories containing the influence of rotatory inertia and shear deformation were derived by various means by E. Reissner [3], [4], A. E. Green [5], R. D. Mindlin [6] and a similar shell theory by F. B. Hildebrand, E. Reissner and G. B. Thomas [7].

In deriving approximate equations of coupled longitudinal and radial motions in an elastic rod, Mindlin and Herrmann [8] have employed the three-dimensional energy expressions and stress-strain relations.

The purpose of the present paper is to demonstrate, with the example of a rod theory, how G. Green's method of deriving the general three-dimensional theory, may be used in deriving approximate theories of motion.

¹ See Historical Introduction in reference [1]. Numbers in brackets refer to the Bibliography at the end of the paper.

7

Shortly after the three-dimensional theory had been established, G. Green [9] proposed a new method of deriving these equations from the principle of conservation of energy. Later, Lord Kelvin [10] elaborated on the justification of Green's procedure within the framework of the laws of thermodynamics; but ever since its inception, Green's approach has remained a controversial issue. De Saint-Venant [11] termed it only a chain of arbitrary assumptions. In recent times, despite its elegance, it has been criticized severely by Truesdell [12], chiefly because of its inability to encompass as many phenomena as an approach starting from the Newtonian laws. Even though Green's formalism does not provide full physical insight, it has merits in its expediency and economy in arriving at a formally complete and consistent theory, within the framework of starting assumptions. The term "consistency" of an approximate theory is used here with particular reference to the principle of conservation of energy. In the absence of heat, the "stresses" of any approximate theory must be derivable from a potential, which imposes restrictions on possible stress-strain relations. This type of restriction leads to the requirement that the differential operator matrix of the displacement equations of equilibrium or of motion must be symmetric, as was pointed out by Vlasov [13]. For example, Vlasov has shown that Love's shell theory² does not satisfy the requirement.

This restriction was also overlooked in the recent paper by Mindlin and Herrmann [8], where certain constants were introduced into the stress-displacement relations in a manner which made the differential operator matrix of the displacement equations of motion asymmetric.

In the present paper it is shown how these constants may be introduced into the stress-displacement relations so as to keep the matrix symmetric.

² See chapter 24 of reference [1].

Even though the displacement equations of motion differ from those of [8], the velocity equation is the same, that is, the wave velocities have the same values as all those presented in [8].

In the first section of the present paper, G. Green's method is used in deriving the equations of three-dimensional linear elasticity in a manner employed by Professor R. D. Mindlin in the seminar in theory of elasticity at Columbia University.

In the second section, an approximate theory of compressional motions in an elastic solid rod is derived, using Green's method as a guide. The starting assumptions are the same as those in [8] and at various stages of the development attention is drawn to analogies with the general three-dimensional theory.

Classical Linear Theory of Elasticity

We consider a volume V of a body of mass density ρ , bounded by a surface S . We shall assume that the total energy in V is composed of the sum of the kinetic energy T and the internal energy W , which are, in the linear theory

$$T = \int_V T^* dv \quad (1)$$

$$W = \int_V W^* dv \quad (2)$$

where dv is the element of volume, T^* the kinetic energy per unit of volume and W^* the internal energy per unit of volume.

Let the body be acted upon by body forces per unit of mass \underline{F} and surface tractions per unit of area \underline{T}_n , n being the outward drawn normal to the tangent plane and let \underline{u} be the displacement produced.

Neglecting thermal effects, the law of conservation of energy is then³

$$\dot{T} + \dot{W} = \int_V \rho \underline{F} \cdot \dot{\underline{u}} dv + \int_S \underline{T}_n \cdot \dot{\underline{u}} ds \quad (3)$$

That is, the rate of increase of the total energy in the body is equal to the rate at which external forces do work on the body.

Let $\underline{\xi}$ designate the strain dyadic, which is the symmetric part of the deformation dyadic $\underline{\nabla} \underline{u}$, that is,

$$\underline{\xi} = \frac{1}{2} (\underline{\nabla} \underline{u} + \underline{u} \underline{\nabla}) \quad (4)$$

Following Green, W^* is assumed to be a single-valued function of $\underline{\xi}$

$$W^* = W^*(\underline{\xi}) \quad (5)$$

The time rate of change of W^* will thus be

$$\dot{W}^* = \frac{\partial W^*}{\partial \underline{\xi}} : \dot{\underline{\xi}} \quad (6)$$

³ The notation employed in this section is that of reference [14].

The kinetic energy density T^* is given in the linear theory by

$$T^* = \frac{1}{2} \rho \dot{\underline{u}} \cdot \dot{\underline{u}} \quad (7)$$

and its time rate of change by

$$\dot{T}^* = \rho \dot{\underline{u}} \cdot \ddot{\underline{u}} \quad (8)$$

Substituting (6) and (8) into (3) we have

$$\int_V \left[\rho \dot{\underline{u}} \cdot \ddot{\underline{u}} + \frac{\partial W}{\partial \underline{\xi}} : \dot{\underline{\xi}} \right] dv = \int_V \underline{F} \cdot \dot{\underline{u}} dv + \int_S \underline{T}_n \cdot \dot{\underline{u}} ds \quad (9)$$

Since $\frac{\partial W}{\partial \underline{\xi}}$ is symmetric

$$\frac{\partial W}{\partial \underline{\xi}} : \dot{\underline{\xi}} = \frac{\partial W}{\partial \underline{\xi}} : \nabla \dot{\underline{u}} \quad (10)$$

because $\underline{\xi}$ is the symmetric part of $\nabla \underline{u}$.

With the aid of the expansion

$$\nabla \cdot (\underline{\Phi} \cdot \underline{a}) = (\nabla \cdot \underline{\Phi}) \cdot \underline{a} + \underline{\Phi} : \nabla \underline{a} \quad (11)$$

where $\underline{\Phi}$ is a dyadic and \underline{a} a vector, and the transformation

$$\int_V \nabla \cdot \underline{\Phi} dv = \int_S \underline{n} \cdot \underline{\Phi} ds \quad (12)$$

\underline{n} being the outward drawn normal unit vector, (9) becomes

$$\int_V \left[\rho \dot{\underline{u}} \cdot \ddot{\underline{u}} - \left(\nabla \cdot \frac{\partial W^*}{\partial \underline{\xi}} \right) \cdot \dot{\underline{u}} \right] dv = \int_V \underline{F} \cdot \dot{\underline{u}} dv + \int_S \left[\underline{T}_n \cdot \dot{\underline{u}} - \underline{n} \cdot \frac{\partial W^*}{\partial \underline{\xi}} \cdot \dot{\underline{u}} \right] ds \quad (13)$$

which must hold for any volume V and for all velocities $\dot{\underline{u}}$, hence,

$$\nabla \cdot \frac{\partial W^*}{\partial \underline{\xi}} = \rho (\underline{F} + \ddot{\underline{u}}) \quad \text{in } V \quad (14)$$

and

$$\underline{n} \cdot \frac{\partial W^*}{\partial \underline{\xi}} = \underline{T}_n \quad \text{on } S \quad (15)$$

Relation (15) defines the dyadic $\frac{\partial W^*}{\partial \underline{\xi}}$, which is called the stress and is designated by the symbol $\underline{\sigma}$. It is that dyadic whose scalar product with \underline{n} , gives the traction \underline{T}_n across the plane whose outward drawn normal is \underline{n} . Equation (14) is, then, the stress equation of motion.

In order to insure uniqueness of solutions of the stress equations of motion, it is necessary to establish an explicit stress-strain relation, whose existence is already implicit in (3) and (5). To this end, we assume W^* to be analytical and expand W^* into a power series of $\underline{\xi}$. Because of the assumed existence of a natural, unstrained state, the linear term in the series vanishes. Further, the third and higher powers of the expansion are neglected on account of the smallness of $\underline{\xi}$. We have thus a quadratic expression for the strain energy

$$W^* = \frac{1}{2} \underline{\xi} : \underline{\underline{C}} : \underline{\xi} \quad (16)$$

where $\underline{\underline{C}}$ is the elasticity tetradic. Equation (16) results in a linear stress-strain relation

$$\frac{\partial W^*}{\partial \underline{\xi}} \equiv \underline{\sigma} = \underline{\underline{C}} : \underline{\xi} \quad (17)$$

Because of the symmetry of $\underline{\sigma}$ and $\underline{\xi}$ the number of independent constants C_{ijkl} which constitute the tetradic $\underline{\underline{C}}$ is 36. Since W^* is a single-valued function, this number is reduced further to 21.

Having thus the definition of stress (15), the stress equations of motion (14) and the stress-strain relations (17), appropriate boundary and initial conditions of the theory should be established, i.e., conditions to be specified on the boundary of the region and at the initial instant, which assure a unique solution.

By an argument due to Neumann⁴, it may be shown that, in the absence

⁴ See p. 176 in reference [1].

of singularities and displacement discontinuities, uniqueness may be assured by specifying (1) one member of each of the three products in $\mathcal{T}_n \cdot \mathcal{U}$ at each point of the surface and (2) the initial displacement and velocity throughout the volume.

A One-Dimensional Theory of Compressional Motions in an Elastic Rod

To illustrate the application of Green's method to an approximate linear theory, a one-dimensional theory governing the compressional motions in an elastic rod will be derived.

Wishing to include in this theory more than is contained in the classical elementary theory, we shall start out from the same assumptions as in paper [8], taking into account the effects of radial inertia and radial shear deformation.

We consider a rod of circular cross-section, $r = a$, and approximate axially symmetric components of displacement u_r , u_θ , u_z , referred to cylindrical coordinates r , θ , z , by the forms

$$\begin{aligned} u_r &\rightarrow r \tilde{u}(z, t) \\ u_\theta &= 0 \\ u_z &\rightarrow w(z, t) \end{aligned} \tag{18}$$

The r -dependence in these approximations has been specified completely, so that integration with respect to r may be performed, thus eliminating r from the resulting equations and reducing the number of space coordinates on which the displacements depend.

From the mathematical point of view we are led to the above approximations by expanding the components of displacement into power series of r , retaining only the first term of each expansion. From the physical point of view the above approximations are justified for the study of compressional motions, because they accommodate the limiting form of the wave motion for long waves in the general three-dimensional theory.

The kinetic energy T of a volume V is, in cylindrical coordinates, given by

$$T = \frac{1}{2} \int_V (\dot{u}_r^2 + \dot{u}_\theta^2 + \dot{u}_z^2) dv \tag{19}$$

and its time rate of change

$$\dot{T} = \int_V (\dot{u}_r \ddot{u}_r + \dot{u}_\theta \ddot{u}_\theta + \dot{u}_z \ddot{u}_z) dv \quad (20)$$

An approximation \bar{T} to the kinetic energy T is obtained by substituting the approximations to the velocities from (18). We obtain

$$\dot{\bar{T}} = \int_0^{2\pi} \int_0^a \int_b^c (\dot{r}^2 \ddot{u} \ddot{u} + \dot{w} \dot{w}') r dr d\theta dz \quad (21)$$

and carrying out the integration

$$\dot{\bar{T}} = 2\pi \int_b^c (\dot{a}^2 \ddot{u} \ddot{u} / 4 + \dot{a}^2 \dot{w} \dot{w}' / 2) dz \quad (22)$$

where $c-b$ is the length of the rod.

The corresponding approximation $\bar{\xi}$ to the strain ξ , calculated on the basis of the approximations to the displacements (18), possesses, in cylindrical coordinates, three different components, namely $\frac{u}{a}$, $ru'/2a$, w' , the prime indicating partial differentiation with respect to z .

The approximation \bar{W}^* to the internal energy W^* , will thus be, following Green,

$$\bar{W}^* = \bar{W}^*(u/a, ru'/2a, w') \quad (23)$$

and the time rate of change of the total internal energy \bar{W}

$$\dot{\bar{W}} = \int_0^{2\pi} \int_0^a \int_b^c \left(\frac{\partial \bar{W}^*}{\partial \frac{u}{a}} \frac{\dot{u}}{a} + \frac{\partial \bar{W}^*}{\partial \left(\frac{r}{2a} u'\right)} \frac{r}{2a} \dot{u}' + \frac{\partial \bar{W}^*}{\partial w'} \dot{w}' \right) r dr d\theta dz \quad (24)$$

or

$$\dot{\bar{W}} = 2\pi \int_b^c (\bar{P} \dot{u}/a + Q \dot{u}' + \bar{P}_z \dot{w}') dz \quad (25)$$

where

$$\left. \begin{aligned} \bar{P} &= \int_0^a \frac{\partial \bar{W}^*}{\partial (\frac{u}{a})} r dr \\ Q &= \int_0^a \frac{\partial \bar{W}^*}{\partial (\frac{1}{2} \frac{r}{a} u)} \frac{r^2}{2a} dr \\ P_z &= \int_0^a \frac{\partial \bar{W}^*}{\partial w} r dr \end{aligned} \right\} \quad (26)$$

In analogy to the three-dimensional theory, the integrals of the set (26) shall be termed "rod-stresses" of the present theory.

Having the expressions (22), (25) for the time rate of change of the kinetic energy \bar{T} and the internal energy \bar{W} , respectively, we proceed to formulate the principle of conservation of energy for a rod of finite length $C - \frac{b}{2}$, expressing that the time rate of change of internal energy must equal the rate at which tractions do work in the displacement of the surface points, assuming the absence of body forces.

Due to the assumption of axially symmetric deformation, the tangential traction \bar{T}_s , at the end sections of the rod, will have radial components only, independent of Θ . The tangential traction \bar{Z} on the cylindrical surface of the rod will have components in the axial direction only and also independent of Θ . The normal component of traction \bar{T}_z on the end section of the rod and the normal component of traction, \bar{R} , on the cylindrical surface of the rod will be also independent of Θ .

The rate at which these tractions do work in the assumed displacements (18) is given by the expression

$$2\pi a \int_{\frac{b}{2}}^C (\bar{R}\dot{u} + \bar{Z}\dot{w}) dz + 2\pi \int_0^a \left(\bar{T}_s r a \dot{u} + \bar{T}_z \dot{w} \right) r dr \quad (27)$$

and the principle of conservation of energy takes the form

$$\begin{aligned}
& 2\pi \int_b^c \left(a^2 \dot{u} \ddot{u} / 4 + a^2 \dot{w} \ddot{w} / 2 \right) dz + 2\pi \int_b^c \left(\bar{P} \dot{u} / a + Q \dot{u}' + P_z \dot{w}' \right) dz \\
& = 2\pi a \int_b^c \left(R \dot{u} + Z \dot{w} \right) dz + 2\pi \int_0^a \left(T_s r \dot{a}' \dot{u} + T_z \dot{w} \right) \Big|_b^c r dr \quad (28)
\end{aligned}$$

Upon integration by parts of the last two terms in the second integral and upon rearrangement, we obtain

$$\begin{aligned}
& \int_b^c \left\{ \dot{u} \left[\int a^2 \ddot{u} / 4 + \bar{P} / a - Q' - aR \right] + \dot{w} \left[\int a^2 \ddot{w} / 2 - P_z' - aZ \right] \right\} dz \\
& = \dot{u} \left[\int_0^a T_s r^2 \dot{a}' dr - Q \right]_b^c + \dot{w} \left[\int_0^a T_z r dr - P_z \right]_b^c \quad (29)
\end{aligned}$$

This relation corresponds to Equation (13) of the three-dimensional theory.

By an analogous argument, we obtain

$$\left. \begin{aligned} Q' - a' \bar{P} + aR &= \int a^2 \ddot{u} / 4 \\ P_z' + aZ &= \int a^2 \ddot{w} / 2 \end{aligned} \right\} \quad (30)$$

$$\left. \begin{aligned} Q &= \int_0^a T_s r^2 \dot{a}' dr \\ P_z &= \int_0^a T_z r dr \end{aligned} \right\} \quad (31)$$

The first two equations (30) are the stress equations of motion, which are the same as those of paper [8], provided \bar{P} is set equal to $P_r + P_\theta$, defined in [8]. The last two equations define the two bar-stresses Q and P_z of the theory and correspond to Equation (15) of the three-dimensional theory.

It should be noted that the method used here does not allow for an identification of the quantity \bar{P} in terms of components of traction.

Comparing (31) with (26) we obtain

$$\left. \begin{aligned} \frac{\partial \bar{W}^*}{\partial \left(\frac{1}{2} r \dot{u}' \right)} &= T_s \\ \frac{\partial \bar{W}^*}{\partial \dot{w}'} &= T_z \end{aligned} \right\} \quad (32)$$

but there is no possibility of relating $\frac{\partial \bar{W}^*}{\partial \left(\frac{u}{a} \right)}$ to a component of traction.

Noteworthy is also that the surface tractions R and Z enter the differential equation of motion in a manner analogous to the appearance of body force in the three-dimensional equations.

The boundary and initial conditions, found by an argument of uniqueness, analogous to the one of three-dimensional theory, are, for the present theory, that it is sufficient to specify

- (1) at each point along the length of the bar, one factor of each of the products $\dot{u}R$ and $\dot{w}P_z$
- (2) at each end of the bar, one member of each of the products $\dot{u}Q$ and $\dot{w}P_z$
- (3) throughout the length of the bar, the initial displacements and velocities.

We proceed to establish the stress-displacement relations, by expanding \bar{W}^* , just as W^* was expanded in the three-dimensional theory. Retaining only the quadratic terms of the expansion, we have

$$\begin{aligned} \bar{W}^* = & \alpha_1 \left(\frac{u}{a} \right)^2 + \alpha_2 \left(\frac{r}{2a} u' \right)^2 + \alpha_3 (w')^2 \\ & + \alpha_4 \frac{u}{a} \frac{r}{2a} u' + \alpha_5 \frac{u}{a} w' + \alpha_6 \frac{r}{2a} u' w' \end{aligned} \quad (33)$$

which yields the stress-displacement relations, in accordance with (26),

carrying out the integration over the radius r

$$\begin{aligned} \bar{P} &= \alpha_1 a u + \alpha_4 \frac{a^2}{6} u' + \alpha_5 \frac{a^2}{2} w' \\ Q &= \alpha_2 \frac{a^2}{4} u' + \alpha_4 \frac{a}{3} u + \alpha_6 \frac{a^2}{3} w' \\ P_z &= \alpha_3 a^2 w' + \alpha_5 \frac{a}{2} u + \alpha_6 \frac{a^2}{6} u' \end{aligned} \quad (34)$$

This completes the formal development of the theory by the method of Green. The 6 constants α_i play the role of the 21 elastic constants c_{ijkl} of the three-dimensional theory. It would not be difficult but it is cumbersome to express α_i in terms of c_{ijkl} . It would be necessary to write down, in cylindrical coordinates, the expression for \bar{W}^* in terms of the components of strain, substitute the approximations (18), obtaining thus \bar{W}^* and compare

with \overline{W}^* given by (33).

If we consider an isotropic rod, characterized elastically by means of Lamé's constants λ and μ , the following values of α_i are readily obtained, in carrying out the procedure outlined above:

$$\left. \begin{aligned} \alpha_1 &= 2(\lambda + \mu) \\ \alpha_2 &= 2\mu \\ \alpha_3 &= \frac{1}{2}(\lambda + 2\mu) \\ \alpha_4 &= 0 \\ \alpha_5 &= 2\lambda \\ \alpha_6 &= 0 \end{aligned} \right\} \quad (35)$$

In paper [8] it has been demonstrated that the present theory predicts wave velocities of first mode which are always higher than those obtained from the general three-dimensional theory.

One possibility of improving the present theory without rendering it more complicated consists in altering the values of α_i , without changing the form of the displacements. Formally, the constants α_i will be determined not in terms of the elastic constants, λ and μ , of the isotropic rod, i.e., matching the strain energy, as was done above, but by matching a number of solutions of basic dynamic problems of the rod, obtained within the present theory and within the three-dimensional theory. This procedure means physically the attempt to diminish the error inherent in the approximate forms of the displacements by making the rod appropriately anisotropic.

Determining α_i in this fashion, we note first that the strain energy expression (33) must be invariant to a reversal of the sense of the z -axis; thus

$$\left. \begin{aligned} \alpha_4 &= 0 \\ \alpha_6 &= 0 \end{aligned} \right\} \quad (36)$$

just as in the isotropic bar.

Considering the problem of pure radial vibration of an infinite isotropic rod, it may be readily verified that the frequency, from the three-dimensional theory, is given by

$$p^2 = \frac{\eta^2}{a^2} \frac{(\lambda+2\mu)}{\rho} \quad (37)$$

where η is the lowest root of

$$\frac{\lambda+2\mu}{2\mu} \eta J_0(\eta) = J_1(\eta) \quad (38)$$

J_0, J_1 being Bessel functions of order zero and one respectively.

In the present theory, the frequency of pure radial vibration is obtained, from

$$-\omega_1 u = \frac{\rho a^2}{4} \ddot{u} \quad (39)$$

as

$$\bar{p}^2 = \frac{4\omega_1}{\rho a^2} \quad (40)$$

The two frequencies are equal if

$$\omega_1 = \frac{\eta^2(\lambda+2\mu)}{4} \quad (41)$$

Wishing to determine the velocity of compressional waves, travelling in the infinite rod, we seek solutions in the form

$$\begin{aligned} u &= A e^{i\gamma(z-ct)} \\ w &= B e^{i\gamma(z-ct)} \end{aligned} \quad (42)$$

with $R=Z=0$

where $\gamma = 2\pi/L$, and c the wave-velocity.

The equations of motion reduce then to two homogeneous, linear, algebraic equations in A and B , whose determinant, set equal to zero, furnishes the frequency or velocity equation

$$[\alpha_2/\rho + 4\alpha_1/a^2\gamma^2\rho - c^2][2\alpha_3/\rho - c^2] - 2\alpha_5^2/a^2\gamma^2\rho = 0 \quad (43)$$

For long waves ($a\gamma \rightarrow 0$), Equation (43) yields

$$c^2 = \frac{8\alpha_1\alpha_3 - 2\alpha_5^2}{4\alpha_1\rho}, \quad c^2 = \infty \quad (44)$$

while the corresponding exact solutions are

$$c^2 = E/\rho, \quad c^2 = \infty \quad (45)$$

Matching the lower velocity we obtain

$$E = 2\alpha_3 - \alpha_5^2/2\alpha_1 \quad (46)$$

We note that Equation (46) is satisfied by the values of α_i in the isotropic rod given by (35). But since α_1 has now been altered in accordance with (41), α_5 has to be changed also, to retain the validity of (46). Expressing the altered value of $\alpha_1 = \chi_1^2(\lambda + \mu)$ as a multiple of its original value $(\lambda + \mu)$, the original value of α_5 has to be changed to $\alpha_5 = 2\lambda\chi_1$, and the original value of α_3 has to be retained. χ_1^2 is determined, in virtue of (41), by

$$\chi_1^2 = \frac{\gamma^2(\lambda + 2\mu)}{8(\lambda + \mu)} \quad (47)$$

For short waves ($a\gamma \rightarrow \infty$), Equation (43) yields

$$c^2 = \alpha_2/\rho, \quad c^2 = 2\alpha_3/\rho \quad (48)$$

while the corresponding exact solutions are

$$c^2 = \chi^2\mu/\rho, \quad c^2 = \mu/\rho \quad (49)$$

the first being the Rayleigh wave velocity where χ^2 is the root of ⁵

⁵ See p. 308 in reference [1].

$$4[(1-\alpha\chi^2)(1-\chi^2)]^{\frac{1}{2}} = (2-\chi^2)^{\frac{1}{2}}, \quad 0 < \chi < 1 \quad (50)$$

and

$$\alpha = \frac{(1-2\nu)}{2(1-\nu)} \quad (51)$$

Since α_3 is already determined, we can match only the lower velocity, obtaining for α_2

$$\alpha_2 = \chi^2 \mu \quad (52)$$

The stress-strain relations of the present theory become thus, in terms of λ, μ

$$\left. \begin{aligned} \bar{P} &= 2\chi_1^2 a (\lambda + \mu) u + \chi a^2 \lambda w' \\ 2P_z &= 2\chi_1 a \lambda u + (\lambda + 2\mu) a^2 w' \\ 4Q &= \chi^2 \mu a^2 u' \end{aligned} \right\} \quad (53)$$

It may be noted that χ_1 has been determined in a different manner in paper [8].

Comparison of the stress-displacement relations (53) with those of paper [8] indicates that the first and the second relations are different, while the third is identical.

From the stress equations of motion (30), with the stress-displacement relations (53), we obtain the displacement equations of motion

$$\begin{aligned} \chi^2 a^2 \mu u''/4 - 2\chi_1^2 (\lambda + \mu) u - \lambda \chi_1 a w' + aR &= \rho a^2 \ddot{u}/4 \\ \lambda \chi_1 a u' + (\lambda + 2\mu) a^2 w''/2 + aZ &= \rho a^2 \ddot{w}/2 \end{aligned} \quad (54)$$

It is observed, that the differential operator matrix of u and w is symmetric. The operator on w in the first equation is the same as the operator on u in the second equation, except for an immaterial opposite

sign. This is not the case in the displacement equations of motion in paper [8]. However, the equation of wave velocities in an infinite rod, deduced from (54), is the same as the one of paper [8]. Thus, all the calculations of wave velocities plotted in [8], retain their validity within the present, modified theory.

Bibliography

- [1] A.E.H. Love, "A Treatise on the Mathematical Theory of Elasticity," (Dover Publications, New York, 1944), 4th Edition.
- [2] J. Boussinesq, "Etude nouvelle sur l'équilibre et le mouvement des corps solides élastique dont certaines dimensions sont très-petites par rapport à d'autres," Journ. de Math., Paris, France, Series 2, Vol. 16, 1871, pp. 125-274, and Series 3, Vol. 5, 1879, pp. 329-344.
- [3] E. Reissner, "The Effect of Transverse Shear Deformation on the Bending of Elastic Plates," Journal of Applied Mechanics, Trans. ASME, Vol. 67, 1945, p. A-69.
- [4] E. Reissner, "On Bending of Elastic Plates," Quarterly of Applied Mathematics, Vol. 5, 1947, pp. 55-68.
- [5] A.E. Green, "On Reissner's Theory of Bending of Elastic Plates," Quarterly of Applied Mathematics, Vol. 7, 1949, pp. 223-228.
- [6] R.D. Mindlin, "Influence of Rotatory Inertia and Shear on Flexural Motions of Isotropic, Elastic Plates," Journal of Applied Mechanics, Trans. ASME, Vol. 73, 1951, pp. 31-38.
- [7] F.B. Hildebrand, E. Reissner and G.B. Thomas, "Notes on the Foundations of the Theory of Small Displacements of Orthotropic Shells," NACA TN 1833, 1949.
- [8] R.D. Mindlin and G. Herrmann, "A One-Dimensional Theory of Compressional Waves in an Elastic Rod," Proc. 1st U.S. National Congress on Applied Mechanics, Chicago, Ill., 1951.
- [9] G. Green, "On the Laws of Reflexion and Refraction of Light at the Common Surface of Two Non-Crystallized Media," Trans. Cambridge Phil. Soc., Vol. 7, 1839.

- [10] Sir W. Thomson (Lord Kelvin), "On the Thermo-elastic and Thermo-magnetic Properties of Matter," Quarterly Journal of Mathematics, Vol. 1, 1885.
- [11] Todhunter and K. Pearson, "History of Elasticity," (Cambridge University Press, 1886), Vol. I, p. 502.
- [12] C. Truesdell, "The Mechanical Foundations of Elasticity and Fluid Dynamics," The Journal of Rational Mechanics and Analysis, Vol. I, April, 1952.
- [13] V.S. Vlasov, "Basic Differential Equations in General Theory of Elastic Shells," Translation. NACA Techn. Memorandum 1241, 1951.
- [14] C.E. Weatherburn, "Advanced Vector Analysis," (G. Bell & Sons, Ltd., London, 1949).

DISTRIBUTION LIST

for

Technical and Final Reports Issued Under
Office of Naval Research Project NR-064-388. Contract Nonr-266(09)

Administrative, Reference and Liaison Activities of ONR

Chief of Naval Research Department of the Navy Washington 25, D.C. Attn: Code 438 (2) Code 416 (1) Code 421 (1)	Commanding Officer Office of Naval Research Branch Office 1000 Geary Street San Francisco 24, California (1)
Director, Naval Research Lab. Washington 25, D.C. Attn: Tech. Info. Officer (9) Technical Library (1) Mechanics Division (2) Code 3834 (J. P. Walsh) (1)	Commanding Officer Office of Naval Research Branch Office 1030 Green Street Pasadena, California (1)
Commanding Officer Office of Naval Research Branch Office 150 Causeway Street Boston 10, Massachusetts (1)	Contract Administrator, SE Area Office of Naval Research c/o George Washington University 707 22nd Street, N.W. Washington 6, D.C. (1)
Commanding Officer Office of Naval Research Branch Office 346 Broadway New York 13, New York (1)	Officer in Charge Office of Naval Research Branch Office, London Navy No. 100 FPO, New York, N.Y. (5)
Commanding Officer Office of Naval Research Branch Office 844 N. Rush Street Chicago 11, Illinois (1)	Library of Congress Washington 25, D.C. Attn: Navy Research Section (2)

Department of Defense

Other Interested Government Activities

GENERAL

Research and Development Board Department of Defense Pentagon Building Washington 25, D.C. Attn: Library (Code 3D-1075) (1)	Armed Forces Special Weapons Project P.O. Box 2610 Washington, D.C. Attn: Col. G. F. Blunda (1)
---	--

ARMY

Chief of Staff
Department of the Army
Research and Development Division
Washington 25, D.C.
Attn: Chief of Res. and Dev. (1)

Office of the Chief of Engineers
Assistant Chief for Works
Department of the Army
Bldg. T-7, Gravelly Point
Washington 25, D.C.
Attn: Structural Branch
(R. L. Bloor) (1)

Office of the Chief of Engineers
Asst. Chief for Military Construction
Department of the Army
Bldg. T-7, Gravelly Point
Washington 25, D.C.
Attn: Structures Branch
(H. F. Carey) (1)

Engineering Research & Development Lab.
Fort Belvoir, Virginia
Attn: Structures Branch (1)

The Commanding General
Sandia Base, P.O. Box 5100
Albuquerque, New Mexico
Attn: Col. Canterbury (1)

Operations Research Officer
Department of the Army
Ft. Lesley J. McNair
Washington 25, D.C.
Attn: Howard Brackney (1)

Office of Chief of Ordnance
Research & Development Service
Department of the Army
The Pentagon
Washington 25, D.C.
Attn: ORDTB (2)

Commanding Officer
Ballistic Research Laboratory
Aberdeen Proving Ground
Aberdeen, Maryland
Attn: Dr. C. W. Lampson (1)

ARMY (cont.)

Commanding Officer
Watertown Arsenal
Watertown, Massachusetts
Attn: Laboratory Division (1)

Commanding Officer
Frankford Arsenal
Philadelphia, Pennsylvania
Attn: Laboratory Division (1)

Commanding Officer
Squier Signal Laboratory
Fort Monmouth, New Jersey
Attn: Components and Materials
Branch (1)

NAVY
Chief of Bureau of Ships
Navy Department
Washington 25, D.C.
Attn: Director of Research (2)

Director
David Taylor Model Basin
Washington 7, D.C.
Attn: Structural Mechanics Div. (2)

Director
Naval Engr. Experiment Station
Annapolis, Maryland (1)

Director
Materials Laboratory
New York Naval Shipyard
Brooklyn 1, New York (1)

Chief of Bureau of Ordnance
Navy Department
Washington 25, D.C.
Attn: Ad-3, Technical Library (1)

Superintendent
Naval Gun Factory
Washington 25, D.C. (1)

Naval Ordnance Laboratory
White Oak, Maryland
RFD 1, Silver Spring, Maryland
Attn: Mechanics Division (2)

Naval Ordnance Test Station
Inyokern, California
Attn: Scientific Officer (1)

NAVY (cont.)

Commander, U.S. N.O.T.S.
Pasadena Annex
3202 E. Foothill Blvd.
Pasadena 8, California
Attn: Code P5507

(1)

Commander, U.S. N.O.T.S.
China Lake, California
Attn: Code 501

(1)

Chief of Bureau of Aeronautics
Navy Department
Washington 25, D.C.
Attn: TD-41, Technical Library

(1)

Naval Air Experimental Station
Naval Air Materiel Center
Naval Base
Philadelphia 12, Pennsylvania
Attn: Head, Aeronautical Materials
Laboratory

(1)

Chief of Bureau of Yards & Docks
Navy Department
Washington 25, D.C.
Attn: Code P-314

(1)

Officer in Charge
Naval Civil Engr. Research and Eval.
Laboratory
Naval Station
Port Hueneme, California

(1)

Commander
U.S. Naval Proving Grounds
Dahlgren, Virginia

(1)

AIR FORCES

Commanding General
U.S. Air Forces
The Pentagon
Washington 25, D.C.
Attn: Research & Development
Division

(1)

Commanding General
Air Materiel Command
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: MCREX-B (E. H. Schwartz)

(1)

AIR FORCES (cont.)

Office of Air Research
Wright-Patterson Air Force Base
Dayton, Ohio
Attn: Chief, Applied Mechanics
Group

(1)

OTHER GOVERNMENT AGENCIES

U.S. Atomic Energy Commission
Division of Research
Washington, D.C.

(1)

Argonne National Laboratory
P.O. Box 5207
Chicago 80, Illinois

(1)

Director
National Bureau of Standards
Washington, D.C.
Attn: Dr. W. H. Ramberg

(1)

U.S. Coast Guard
1300 E Street, N.W.
Washington, D.C.
Attn: Chief, Testing & Developing
Division

(1)

Forest Products Laboratory
Madison, Wisconsin
Attn: L. J. Markwardt

(1)

National Advisory Committee for
Aeronautics
1724 F Street, N.W.
Washington, D.C.

(1)

National Advisory Committee for
Aeronautics
Langley Field, Virginia
Attn: Dr. E. Lundquist

(1)

National Advisory Committee for
Aeronautics
Cleveland Municipal Airport
Cleveland, Ohio
Attn: J. H. Gollins, Jr.

(1)

U.S. Maritime Commission
Technical Bureau
Washington, D.C.
Attn: V. Russo

(1)

Contractors and Other Investigators
Actively Engaged in Related Research

Professor J. R. Andersen Towne School of Engineering University of Pennsylvania Philadelphia, Pennsylvania	(1)	Dr. V. Cadambe Assistant Director of the National Physical Laboratory of India Hillside Road New Delhi 12, India	(1)
Professor Melvin Baron Dept. of Civil Engineering Columbia University New York 27, New York	(1)	Professor George F. Carrier Division of Applied Science Pierce Hall Harvard University Cambridge 38, Massachusetts	(1)
Professor Lynn Beedle Fritz Engineering Laboratory Lehigh University Bethlehem, Pennsylvania	(1)	Dr. David Cheng M. W. Kellogg Company 225 Broadway New York, New York	(1)
Professor C. B. Biezeno Technische Hoogeschool Nieuwe Laan 76 Delft, Holland	(1)	Committee on Government Aided Research Columbia University 313 Low Memorial Library New York 27, New York	(2)
Dr. M. A. Biot 1819 Broadway New York, New York	(1)	Mrs. Hilda Cooper The Dell Searingtown Albertson, Long Island, New York	(1)
Professor R. L. Bisplinghoff Dept. of Aeronautical Engineering Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)	Dr. Antoine E. I. Craya Neyrpic Boite Postale 52 Grenoble, France	(1)
Professor Hans H. Bleich Dept. of Civil Engineering Columbia University New York 27, New York	(1)	Professor J. P. Den Hartog Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)
Professor J. A. Bogdanoff Purdue University Lafayette, Indiana	(1)	Professor Herbert Deresiewicz Dept. of Civil Engineering Columbia University 632 West 125th Street New York 27, New York	(1)
Professor B. A. Boley Dept. of Civil Engineering Columbia University New York 27, New York	(1)	Dr. C. O. Dohrenwend Rensselaer Polytechnic Institute Troy, New York	(1)
Professor P. W. Bridgeman Dept. of Physics Harvard University Cambridge 38, Massachusetts	(1)	Professor T. J. Dolan Dept. of Theoretical and Applied Mechanics University of Illinois Urbana, Illinois	(1)
Professor D. M. Burmister Dept. of Civil Engineering Columbia University New York 27, New York	(1)		

Contractors and Other Investigators Actively Engaged in Related Research (cont.)

Professor Lloyd Donnell Dept. of Mechanics Illinois Institute of Technology Chicago 16, Illinois	(1)	Professor K. O. Friedrichs New York University Washington Square New York, New York	(1)
Professor D. C. Drucker Division of Engineering Brown University Providence 12, Rhode Island	(1)	Professor M. M. Frocht Illinois Institute of Technology Chicago 16, Illinois	(1)
Dr. W. Eckert Watson Scientific Computing Laboratory 612 West 116th Street New York 27, New York	(1)	Professor J. M. Garrelts Dept. of Civil Engineering Columbia University New York 27, New York	(1)
Dr. H. Ekstein Armour Research Foundation Illinois Institute of Technology Chicago 16, Illinois	(1)	Professor J. A. Goff University of Pennsylvania Philadelphia, Pennsylvania	(1)
Engineering Library Columbia University New York 27, New York	(1)	Mr. E. A. Gerber Signal Corps Engineering Labs. Fort Monmouth, New Jersey Watson Area	(1)
Professor E. L. Eriksen University of Michigan Ann Arbor, Michigan	(1)	Mr. Martin Goland Midwest Research Institute 4049 Pennsylvania Kansas City 2, Missouri	(1)
Professor A. C. Eringen Illinois Institute of Technology Chicago 16, Illinois	(1)	Dr. J. N. Goodier Dept. of Engineering Mechanics Stanford University Stanford, California	(1)
Dr. W. L. Esmeijer Voorduinstraat 24 Haarlem, Holland	(1)	Professor L. E. Goodman Dept. of Mechanical Engineering University of Minnesota Minneapolis 14, Minnesota	(1)
Mr. Marvin Forray 1396 East 16th Street Brooklyn 30, New York	(1)	Professor R. J. Hansen Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)
Dr. F. Forscher Westinghouse Atomic Power Division P.O. Box 1468 Pittsburgh 30, Pennsylvania	(1)	Professor R. M. Hermes University of Santa Clara Santa Clara, California	(1)
Professor A. M. Freudenthal Dept. of Civil Engineering Columbia University New York 27, New York	(1)	Professor G. Herrmann Dept. of Civil Engineering Columbia University New York 27, New York	(1)
Professor B. Fried Washington State College Pullman, Washington	(1)		

Contractors and Other Investigators Actively Engaged in Related Research (cont.)

Professor M. Hetényi Northwestern University Evanston, Illinois	(1)	Professor Thomas R. Kane 25-2 Valley Road Drexel Hill, Pennsylvania	(1)
Professor T. J. Higgins Dept. of Electrical Engineering University of Wisconsin Madison 6, Wisconsin	(1)	Professor K. Klotter Stanford University Stanford, California	(1)
Professor N. J. Hoff Dept. of Aeronautical Engineering Polytechnic Institute of Brooklyn 99 Livingston Street Brooklyn 2, New York	(1)	Professor W. J. Krefeld Dept. of Civil Engineering Columbia University New York 27, New York	(1)
Professor M. B. Hogan University of Utah Salt Lake City, Utah	(1)	Professor B. J. Lazan Dept. of Materials Engineering University of Minnesota Minneapolis 14, Minnesota	(1)
Professor D. L. Holl Iowa State College Ames, Iowa	(1)	Professor E. H. Lee Division of Applied Mathematics Brown University Providence 12, Rhode Island	(1)
Dr. J. H. Hollomon General Electric Research Labs. 1 River Road Schenectady, New York	(1)	Professor George Lee Rensselaer Polytechnic Institute Troy, New York	(1)
Professor W. H. Hoppmann Dept. of Applied Mechanics The Johns Hopkins University Baltimore, Maryland	(1)	Professor J. M. Lessells Dept. of Mechanical Engineering Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)
Dr. Gabriel Horvay Knolls Atomic Power Laboratory General Electric Company Schenectady, New York	(1)	Library, Engineering Foundation 29 West 39th Street New York, New York	(1)
Institut de Mathématiques Université post. fah 55 Skoplje, Yugoslavia	(1)	Professor Paul Lieber Dept. of Engineering Rensselaer Polytechnic Institute Troy, New York	(1)
Professor L. S. Jacobsen Dept. of Mechanical Engineering Stanford University Stanford, California	(1)	Dr. Hsu Lo Purdue University Lafayette, Indiana	(1)
Professor Bruce G. Johnston University of Michigan Ann Arbor, Michigan	(1)	Professor C. T. G. Looney Dept. of Civil Engineering Yale University New Haven, Connecticut	(1)

Contractors and Other Investigators Actively Engaged in Related Research (cont.)

Dr. J. L. Lubkin Midwest Research Institute 4049 Pennsylvania Kansas City 2, Missouri	(1)	Professor N. M. Newmark 207 Talbot Laboratory University of Illinois Urbana, Illinois	(1)
Professor J. F. Ludloff School of Aeronautics New York University New York 53, New York	(1)	Professor Jesse Ormondroyd University of Michigan Ann Arbor, Michigan	(1)
Professor J. N. Macduff Rensselaer Polytechnic Institute Troy, New York	(1)	Professor W. Osgood Illinois Institute of Technology Chicago 16, Illinois	(1)
Professor C. W. MacGregor University of Pennsylvania Philadelphia, Pennsylvania	(1)	Dr. George B. Pegram 313 Low Memorial Library Columbia University New York 27, New York	(1)
Professor Lawrence E. Malvern Dept. of Mathematics Carnegie Institute of Technology Pittsburgh 13, Pennsylvania	(1)	Dr. R. P. Petersen Director, Applied Physics Division Sandia Laboratory Albuquerque, New Mexico	(1)
Professor J. H. Marchant Brown University Providence 12, Rhode Island	(1)	Mr. R. E. Peterson Westinghouse Research Laboratories East Pittsburgh, Pennsylvania	(1)
Professor J. Marin Pennsylvania State College State College, Pennsylvania	(1)	Professor A. Phillips School of Engineering Stanford University Stanford, California	(1)
Dr. W. P. Mason Bell Telephone Laboratories Murray Hill, New Jersey	(1)	Professor Gerald Pickett Dept. of Mechanics University of Wisconsin Madison 6, Wisconsin	(1)
Professor R. D. Mindlin Dept. of Civil Engineering Columbia University 632 West 125th Street New York 27, New York	(15)	Dr. H. Poritsky General Engineering Laboratory General Electric Company Schenectady, New York	(1)
Dr. A. Nadai 136 Cherry Valley Road Pittsburgh 21, Pennsylvania	(1)	Professor W. Prager Graduate Division of Applied Mathematics Brown University Providence 12, Rhode Island	(1)
Professor Paul M. Naghdi Dept. of Engineering Mechanics University of Michigan Ann Arbor, Michigan	(1)	Dr. Frank Press Lamont Geological Observatory Palisades, New York	(1)

Contractors and Other Investigators Actively Engaged in Related Research (cont.)

RAND Corporation 1500 4th Street Santa Monica, California Attn: Dr. D. L. Judd	(1)	Dr. Daniel T. Sigley American Machine and Foundry Company 511 Fifth Avenue New York, New York	(1)
Dr. S. Raynor Armour Research Foundation Illinois Institute of Technology Chicago 16, Illinois	(1)	Professor C. B. Smith Department of Mathematics Walker Hall University of Florida Gainesville, Florida	(1)
Professor E. Reissner Dept. of Mathematics Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)	Professor C. R. Soderberg Dept. of Mechanical Engineering Massachusetts Institute of Technology Cambridge 39, Massachusetts	(1)
Professor H. Reissner Polytechnic Institute of Brooklyn 99 Livingston Street Brooklyn 2, New York	(1)	Professor R. V. Southwell Imperial College of Science and Technology South Kensington London S.W. 7, England	(1)
Dr. Kenneth Robinson Combustion Engineering, Inc. 200 Madison Avenue New York 16, New York	(1)	Professor E. Sternberg Illinois Institute of Technology Chicago 16, Illinois	(1)
Professor Leif Rongved Dept. of Engineering Mechanics Pennsylvania State College State College, Pennsylvania	(1)	Professor J. J. Stoker New York University Washington Square New York, New York	(1)
Professor M. A. Sadowsky Dept. of Mechanics North Hall Rensselaer Polytechnic Institute Troy, New York	(1)	Mr. R. A. Sykes Bell Telephone Laboratories Murray Hill, New Jersey	(1)
Professor M. G. Salvadori Dept. of Civil Engineering Columbia University New York 27, New York	(1)	Professor P. S. Symonds Brown University Providence 12, Rhode Island	(1)
Mr. Arnold Schacknow 20-35 Seagirt Boulevard Far Rockaway, New York	(1)	Professor J. L. Synge Dublin Institute for Advanced Studies School of Theoretical Physics 64-65 Merrion Square Dublin, Ireland	(1)
Dr. F. S. Shaw Superintendent Structures & Materials Division Aeronautical Research Laboratories Box 4331, G.P.O. Melbourne Victoria, Australia	(1)	Professor F. K. Teichmann Dept. of Aeronautical Engineering New York University University Heights, Bronx New York, New York	(1)

Contractors and Other Investigators Actively Engaged in Related Research (cont.)

Professor S. P. Timoshenko School of Engineering Stanford University Stanford, California	(1)	Professor Alexander Weinstein Institute of Applied Mathematics University of Maryland College Park, Maryland	(1)
Professor C. A. Truesdell Graduate Institute for Applied Mathematics Indiana University Bloomington, Indiana	(1)	Professor Dana Young Yale University Winchester Hall 15 Prospect Street New Haven, Connecticut	(1)
Professor Karl S. Van Dyke Department of Physics Scott Laboratory Wesleyan University Middletown, Connecticut	(1)		
Dr. I. Vigness Naval Research Laboratory Anacostia Station Washington, D.C.	(1)		
Dr. Leonardo Villena Av. de La Habana. 147 Madrid, Spain	(1)		
Professor E. Volterra Rensselaer Polytechnic Institute Troy, New York	(1)		
Mr. A. M. Wahl Westinghouse Research Laboratories East Pittsburgh, Pennsylvania	(1)		
Professor C. T. Wang Dept. of Aeronautical Engineering New York University University Heights, Bronx New York, New York	(1)		
Dr. R. L. Wegel RFD 2 Peekskill, New York	(1)		
Professor E. E. Weibel University of Colorado Boulder, Colorado	(1)		
Professor Jerome Weiner Dept. of Civil Engineering Columbia University New York 27, New York	(1)		